

www.TURNSTILES.us STADIUM FASTPASS SERIES TURNSTILES AND ADA GATES
Stadium Fastpass Series™, Models FP500-T, FP500-TP (Subject to change without notice.)
CABINET-STYLE, WAIST-HIGH TURNSTILES
TURNSTILE SPECIFICATION: SECTION 10450

1.00 PART I GENERAL

- 1.01 Drawings and general provisions as specified apply to this section.
- 1.02 Product Data – Manufacturer’s general description for each item and related components.
For specific information, see catalog.
- 1.03 Shop drawings submitted upon request.
- 1.04 Turnstiles available in mechanical and electronic in clockwise, counter-clockwise, or bi-directional movement of travel.

2.00 PART II PRODUCTS

2.01 Turnstile models as distributed by www.TURNSTILES.us.

2.02 STADIUM FASTPASS™ SERIES

A. FP500-T Ticket Box – Bolt down

- 1. Cabinet: Outer shell, inner shell, cover 14 gauge, base 11 gauge. All 304 stainless steel, No. 4 satin finish.
- 2. Arms: 1-5/16” (33mm) diameter, 12 gauge. Hub 4-1/2” (114mm) O.D. All materials are 304 stainless steel, No. 4 satin finish.
- 3. Control Head: Self-centering, adjustable hydraulic shock suppression, hardened tool steel locking bars, cam and roller assemblies, permanently lubricated bearings.
- 4. Height: 37” (940mm); Width: 33-1/4” (692mm); Depth: 8-5/8” (225mm).
- 5. Standard Finish: 304 stainless steel, No. 4 satin finish.
- 6. Keylock: control direction of travel manually by key to lock or unlock, or may be used to override electronic controls.
- 7. Equipped with locked ticket stub compartment 6”x8”x20”. Unit can be converted to Scanner cabinet.
- 8. For options, see Section 2.03.

B. FP500-TP Portable Ticket Box

- 1. Cabinet: Outer shell, inner shell, cover 14 gauge, base and rail 11 gauge. All 304 stainless steel, No. 4 satin finish.
- 2. Arms: 1-5/16” (33mm) diameter, 12 gauge. Hub 4-1/2” (114mm) O.D. All materials No. 4 satin finish.
- 3. Control Head: Self centering, adjustable hydraulic shock suppression, hardened tool steel locking bars, cam and roller assemblies, permanently lubricated bearings.
- 4. Height 37” (940mm); Width 33-1/4” (692mm); Depth: 8-5/8” (225mm).
- 5. Standard Finish: 304 stainless steel, No. 4 satin finish.
- 6. Keylock: control direction of travel manually by key to lock or unlock, or may be used to override electronic controls.
- 7. Equipped with locked ticket stub compartment 6”x8”x20”. Unit can be converted to Scanner cabinet.
- 8. For options, see Section 2.03.

2.03 OPTIONS

- A. All units available in clockwise, counter-clockwise, or bi-directional passage.
 - 1. Electronic lock modules include heavy-duty 24 VDC pull type industrial solenoids, and card reader interface. One module for one-way control, two modules for bi-directional control. Available in each separate direction, fail-safe (open on power failure) or Fail-Lock (lock on power failure) modes. Not available on portable models.
 - 2. Interfacing to card readers, computer attendance systems, coin and token acceptors, push buttons, and wireless remote controls.
 - 3. Electronic 6 digit resetable counter with LCD display and ten year lithium battery.
- B. Additional options available on request.

3.00 PART III EXECUTION

- 3.01 Purchaser to install units in accordance with manufacturer’s shop drawings and installation manual.
- 3.02 Warranty: Units are warranted against defects in materials and workmanship for a period of one year from date of delivery.
See Warranty information for specific details.

