www.TURNSTILES.us

enterprise access control

www.TURNSTILES.us V-Smart™

support for contactless smart cards

FEATURES

- Industry's most accurate finger scan algorithm (#1 at FVC 2002 and FVC 2004)
- RoHS Compliant
- · New blue LED power signal
- · USB communications to AUX port
- Unlimited users finger scan templates are stored on the smart card
- Supports iCLASS™ or MIFARE® contactless smart card technology
- · Dual-factor authentication
- VeriAdmin software which is included free of charge, offers a simple approach to template management (enrollment, distribution) and reader configuration
- · Compact modular design
- Intuitive user interface with multi-colored LED signals and tone signals
- Flexible communication options supporting Wiegand formats up to 64 bits
- · Duress finger option

Dual-verification finger-scan reader combines the high security of biometric matching technology with support for contactless smart cards

One-to-one biometric template verification provides traditional access control customers fast throughput and individual privacy



www.TURNSTILES.us V-Smart™

TECHNICAL INFORMATION

DIMENSIONS

Length: 130 mm (5.12") Width: 118 mm (4.65") Depth: 63.5 mm (2.5")

COMMUNICATIONS:

Pigtail wire connection for RS-232, RS-485, Wiegand IN/OUT. USB aux port connection

ALGORITHM TYPE: Verification (1:1):

Enrollment Time: < 3 seconds Verification Time: < 2 seconds (EER) Equal Error Rate (FAR=FRR): 0.1% Adjustable FAR and FRR Template Size: ~ 350 bytes

VOLTAGE:

9-24 VDC

CURRENT DRAW:

Idle: 0.20 amps @12 VDC Max: 0.50 amps @ 12 VDC

MOUNTING:

Flat surface, double-gang compatible. Mounting plate will accept #6 screws or bolts. Clearance hole diameter is 0.155".

OUTDOOR ENCLOSURE AVAILABLE:

Call for information.

OPERATING TEMPERATURE:

0° - 60°C

OPTIONAL BIO-SDK AVAILABLE:

Development software CD (supports all Bioscrypt products)

ORDERING INFORMATION

V-SMART MIFARE® ORDERING INFORMATION:

CERTIFICATIONS:

FCC, CE, UL294, cUL, RoHS

CARDS SUPPORTED:

GemEasy 8000, HID 1430 and HID 1431 (request HID cards unprogrammed on the MIFARE® side), IDentiSMART Series by IDenticard. Contact Bioscrypt for a complete list of supported cards

V-Smart-A, R:

Finger scan reader with integrated GemPlus MIFARE® contactless smart card reader

DESKTOP-VT-A, R:

V-SMART-A,R reader mounted on a plastic stand, power supply, and CD

DEMO-VT-A, R:

V-SMART-A, R reader mounted on stand, power supply, case, and 5 MIFARE® cards

V-SMART ICLASS™ ORDERING INFORMATION:

CERTIFICATIONS:

FCC, CE, UL294, cUL

CARDS SUPPORTED:

HID iCLASS™ or Honeywell Access Systems OmniSmart™ contactless (16kbits, 16 App) smart cards

V-SMART-A-H, R:

Finger scan reader with integrated iCLASS™ contactless smart card reader

DESKTOP-VT-i, R:

V-SMART-A-H, R reader mounted on a plastic stand, power supply and CD

DEMO-VT-i, R:

V-SMART-A-H, R reader mounted on stand, power supply, case, and 5 iCLASS™ cards



www.TURNSTILES.us

8641 South Warhawk Road Conifer, CO 80433 (303) 670-1099 x11 Patrick.McAllister@Turnstiles.us