

## PHYSICAL ACCESS SOLUTIONS



pivCLASS®  
Biometric Reader

Meets NIST assurance-level requirements for these areas:

- “Unrestricted” Areas
- “Controlled” Areas
- “Limited” Areas
- “Exclusion” Areas



### BIOMETRIC READER FOR “EXCLUSION” AREAS FOR HIGH SECURITY, INTEROPERABILITY AND COMPLIANCE

- **Part of an integrated solution from a single, trusted provider** – Enables compliance per NIST SP 800-116 guidelines and the TWIC Reader Specification.
- **Contact biometric (BIO) reader solution for “Exclusion” security areas** – Meets NIST’s “Exclusion” assurance-level requirements with three-factor PIV + PIN + BIO authentication.
- **Supports multiple card types** – Works with PIV, PIV-I, CAC, CIV (a.k.a., PIV-C), TWIC, FRAC and iCLASS® cards for easy, phased transitions from legacy technology to new PKI-enabled smart cards.

#### ADDITIONAL PRODUCT FEATURES:

- Architected for maximum security and affordability, the reader utilizes the pivCLASS Authentication Module to provide cryptographic functionality and to pass Wiegand-formatted data to the PACS controller. Locating the critical security operations within the secure perimeter (rather than on the attack side of the door) increases security and reader affordability.
- Up to two pivCLASS readers can connect to a pivCLASS Authentication Module via four-wire RS-485 communication to the reader, typically enabling facilities to reuse much of their existing wiring.
- Mountable on single- and double-gang boxes with a width of roughly a double-gang device.
- Available with either a pigtail or terminal strip wiring termination.
- Supports CHUID, CAK, PKI + PIN and PIV + PIN + BIO authentication modes, which can be dynamically changed from a central location.

HID Global’s pivCLASS® Government Solutions portfolio makes it possible for facilities to upgrade their existing physical access control system (PACS) to achieve FIPS 201 compliance.

The pivCLASS Biometric Reader (RKCLB40) delivers the “Exclusion” assurance level defined in the National Institute of Standards and Technology (NIST) SP 800-116 guidelines. This reader works with the pivCLASS Authentication Module (PAM) to perform three authentication checks: **PIV + PIN + BIO**.

**PIV:** The pivCLASS system first determines the validity of the PIV card and its certificates using public key cryptography-based authentication. For instance, the system verifies the digital signature and performs path validation on the PIV authentication certificate and the biometric template data object.

**PIN:** As part of the PIV verification process, the cardholder must enter a PIN to unlock the card in order to retrieve the PIV certificate and biometric template.

**BIO:** After the card and its contents have been validated, the pivCLASS system compares the reference biometric template stored on the card with the biometric sample from the live finger.

If successful, three factors of authentication have been achieved. Only then will the pivCLASS system pass the appropriate cardholder ID data to the PACS controller for an access decision.

This three-factor authentication protects against cards that have been revoked, counterfeited, altered, copied, cloned, lost, stolen or shared.

Optionally, the reader’s authentication mode can be lowered by the PAM to accommodate areas with reduced security requirements. This authentication mode can be dynamically changed from a central location in response to threat level, time of day or day of week.

The pivCLASS Biometric Reader is guaranteed to meet the stringent specifications for operation, reliability and interoperability with other Genuine HID® products.

## SPECIFICATIONS

<b>Model Name</b>	<b>RKCLB40</b>
<b>Base Part Number</b>	924NPR
<b>Specifications</b>	Final
<b>13.56 MHz Card Compatibility</b>	PKI-Based FIPS-201 Credentials including PIV, PIV-I, CIV, CAC, TWIC and FRAC
<b>System Requirements</b>	These readers require HID Global's pivCLASS Authentication Module (M2000) to support FICAM compliance
<b>Typical Contactless Read Range<sup>1</sup></b>	FIPS 201 type cards can be read using either the contact or contactless card interface Biometric authentication only available on the contact interface per FIPS 201
	<b>FIPS 201 Type Cards, Contactless Interface PIV, PIV-I, CIV, CAC, TWIC and FRAC</b>
FIPS-201	2.0" (5 cm)
	<b>13.56 MHz Single Technology ID-1 Cards – SIO Data Model</b>
iCLASS® Seos®	2.0" (5 cm)
iCLASS®	5.5" (14 cm)
MIFARE DESFire EV1	2.0" (5 cm)
MIFARE® Classic	5.1" (13 cm)
<b>Mounting</b>	Double-gang size; designed to mount on double (preferable for stable wall mount) or single-gang switch box
<b>Color</b>	Black
<b>Keypad</b>	Yes (illuminated, 4 x 3)
<b>Dimensions</b>	4.8" x 6.1" x 1.2" (12.2 cm x 15.6 cm x 3.0 cm)
<b>Product Weight (Pigtail)</b>	17.0 oz (484 g)
<b>Product Weight (Terminal Strip)</b>	16.0 oz (454 g)
<b>Operating Voltage Range</b>	+12VDC
<b>Current Draw - Normal Standby Current<sup>2</sup></b>	165 mA
<b>Current Draw - Maximum Average<sup>3</sup></b>	215 mA
<b>Current Draw - Peak<sup>4</sup></b>	275 mA
<b>Operating Temperature</b>	14° to 122° F (-10° to 50° C)
<b>Operating Humidity</b>	5% to 95% relative humidity non-condensing
<b>Storage Temperature</b>	-67° to 185° F (-55° to 85° C)
<b>Environmental Rating</b>	UL 294 and IP55 outdoor ratings
<b>Fingerprint Biometric Sensor Type</b>	Optical
<b>Transmit Frequency</b>	13.56 MHz
<b>Protocol</b>	HID Global pivCLASS Protocol, CoreStreet Reader Protocol
<b>Cable Distance</b>	Six conductor connections per reader: full duplex four-wire RS485 for communication (500 ft [152m], 22AWG), (300 ft [91m], 24AWG); two wires for power (500 ft [152m], 22AWG)
<b>Wiring Connection</b>	Pigtail or Terminal Strip
<b>Certifications</b>	FICAM tested, UL294 (U.S. & Canada), FCC Certification (U.S.), RoHS2
<b>Housing Material</b>	UL94 Polycarbonate
<b>UL Ref Number</b>	RKCLB40E
<b>Warranty</b>	Warranted against defects in materials and workmanship (see complete warranty policy for details)