

PHYSICAL ACCESS SOLUTIONS



THE PROXPASS® II IS AN ACTIVE TAG SPECIFICALLY DESIGNED FOR VEHICLE ACCESS CONTROL.

Features:

- Access door permits convenient battery replacement.
- Provides up to six foot read range.
- Velcro backing attaches easily to interior of vehicle windshield.
- Attractive, durable sealed case.
- Compatible with MaxiProx® reader and card formats up to 37-bits in length.
- Two to five year battery life, depending on usage.
- Competitively priced as compared to VHF vehicle tags.

- **Easily Administered** – A cross-reference list correlating the external card number and the programmed ID number provides easy system administration.
- **Security** – Offers over 137 billion unique codes.
- **Long Life** – Dual battery design and low current draw allows two to five years with typical usage.
- **Durability** – Rugged, UV-resistant, sonic-welded polycarbonate case is also weather resistant.

Providing convenient access control for parking and fleet management applications, ProxPass II is an ideal augmentation to an existing or new HID proximity installation. The ProxPass II can be encoded with HID formats up to 37-bits in length used by HID proximity cards.

SPECIFICATIONS

ProxPass® II Active Tag

Typical Maximum* Read Range	Up to 6' (1.8 m)
Supported Formats	Supports all HID formats up to 37-bits in length. Note: This product does not support Corporate 1000 48-bit formats or any format greater than 37-bits in length.
Dimensions	3.625" x 2.65" x 0.30" (9.25cm x 6.75cm x .76cm)
Mounting Location	Interior windshield, driver's side, upper or lower corner Note: Ideal mounting location is on interior windshield glass. Mounting on metal will degrade performance.
Operating Temperature	-22° to 185° F (-30° to +85° C)
Options	External numbering
Environmental	5 - 95% RH, non-condensing (Not for marine usage)
Warranty	One year warranty against defects in materials and workmanship (see complete sales policy for details)

NOTES:
*Dependent on local installation conditions.

